



FEATURES & BENEFITS

- Compatible with rainscreen applications via extended base, compensating for cavity between sheathing and cladding.
- Patented design eliminates leaky joints while maximizing water protection with one-piece molded base and built-in drip edge.
- Integrity of the building envelope is maintained via a removable hood for simple duct cleaning.
- Suitable for intake and exhaust applications.
- Over-sized flange ensures watertight installation.
- Made with UV-protected durable polymer resin.
- Highly resistant to mechanical impact including a built-in bird screen.
- Quick and easy installation.
- * For dryer applications we recommend the no screen 'NS' model.

TECHNICAL DRAWINGS





COLOURS

- Black (25)
- Light Grey (31)
- Dark Grey (28)

PART NUMBER/SIZING

• Taupe (23)



- Tan (45)
- Dark Brown (68)
- Snow White (01)



Part # Screen	Part # No Screen	Size	Free Area	Description	Pkg
WC3	WC3NS	3" Dia.	7.7 sq. in.	Use 3" dia. ducting	25/box
WC4	WC4NS	4" Dia.	9.5 sq. in.	Use 4" dia. ducting	25/box
WC5	WC5NS	5" Dia.	19.6 sq. in.	Use 5" dia. ducting	10/box
WC6	WC6NS	6" Dia.	28.3 sq. in.	Use 6" dia. ducting	10/box
WC7	WC7NS	7" Dia.	38.5 sq. in.	Use 7" dia. ducting	2/box
WC8	WC8NS	8" Dia.	46.8 sq. in.	Use 8" dia. ducting	2/box

RANGE HOOD VENTS

Part #	Duct Boot	Free Area
WC310	3" x 10"	30.2 sq. in.

WC310K 3.25" x 10" 30.2 sq. in.

Description

Wall Cap Vent: use with 3" x 10" register boot or slab duct Range Hood Vent: use with 3.25" x 10" kitchen transition

Pkg

18/box 18/box

boot or slab duct

APPLICATIONS



FA t in







