



FEATURES & BENEFITS

- Compatible with rainscreen applications via extended base, compensating for cavity between sheathing and cladding.
- Patented design eliminates leaky joints while maximizing water protection with one-piece molded base and built-in drip edge.
- Integrity of the building envelope is maintained via a removable hood for simple cleaning or replacement.
- Suitable for intake and exhaust applications.
- Over-sized flange ensures watertight installation.
- Spring loaded damper.
- Made with UV-protected durable polymer resin.
- Highly resistant to mechanical impact including a built-in bird screen.
- Quick and easy installation.
- * For dryer applications we recommend the no screen 'NS' model.

TECHNICAL DRAWINGS





COLOURS

- Black (25)
- Light Grey (31)
- Dark Grey (28)
- Taupe (23)



- Tan (45)
- Dark Brown (68)
- Snow White (01)



PART NUMBER/SIZING

	Part # No Screen	Size	Free Area	Description	Pkg
WC4S	WC4SNS	4" Dia.	9.5 sq. in.	Use 4" dia. ducting	25/box
WC5S	WC5SNS	5" Dia.	19.6 sq. in.	Use 5" dia. ducting	10/box
WC6S	WC6SNS	6" Dia.	28.3 sq. in.	Use 6" dia. ducting	10/box



Fin





