FEATURES & BENEFITS

- Compatible with rainscreen applications via extended base, compensating for cavity between sheathing and cladding.
- Patented design eliminates leaky joints while maximizing water protection with one-piece molded base and built-in drip edge.
- Integrity of the building envelope is maintained via a removable hood for simple duct cleaning.
- Suitable for intake and exhaust applications.
- Over-sized flange ensures watertight installation.
- Made with UV-protected durable polymer resin.
- Highly resistant to mechanical impact including a built-in bird screen.
- Quick and easy installation.

COLOURS

• Black (25)

- Tan (45)
- Light Grey (31)

Dark Brown (68)Snow White (01)

- Dark Grey (28)
- Taupe (23)

APPLICATIONS

• Dryer Venting

PART NUMBER/SIZING

Part #	Size	Free Area	Description	Pkg
WC3NS	3" Dia.	7.7 sq. in.	Use 3" dia. ducting	25/box
WC4NS	4" Dia.	9.5 sq. in.	Use 4" dia. ducting	25/box
WC5NS	5" Dia.	19.6 sq. in.	Use 5" dia. ducting	10/box
WC6NS	6" Dia.	28.3 sq. in.	Use 6" dia. ducting	10/box
WC7NS	7" Dia.	38.5 sq. in.	Use 7" dia. ducting	2/box
WC8NS	8" Dia.	46.8 sq. in.	Use 8" dia. ducting	2/box

TECHNICAL DRAWING

